BRYMEN®
BRIGHT PEOPLE'S CHOICE

BM869s

Professional Multimeters

HIGH ACCURACY	0.02% Basic DCV Accuracy; 1µVDC Best Resolution
ANALOG BAR-GRAPH	Fast Update Rate 60/Sec
LARGE 500,000 Counts LCD Display	5/Sec Fast Nominal Update Rate
ASIC TECHNOLOGY	More Functions & Features At Affordable Prices
DUAL DIGITAL DISPLAY	Simultaneously View Relevant Parameters In Complementary Display
T1-T2 TYPE-K TEMPERATURE	2 Channel Measurements, Selectable °C & °F Readings
DIODE TEST	For Checking Diodes And Rectifiers
DATA HOLD	Freezes The Displaying Reading For Later View
MAX MIN AVG RECORD	Record Max, Min & AVG Readings; Auto-Ranging
nS CONDUCTANCE	nS=1/GΩ Virtually Extends Resistance Measurement To The Order Of GΩ. It Is Useful For Leakage Measurements
FAST AUDIBLE CONTINUITY	For Quick Open-Short Tests On Switches, Fuses, And Wires
%4-20mA LOOP CURRENT	For Process Control
X-SPEED CAPACITANCE	X-Speed Measures Up To 25mF Only In A Few Seconds; 1kV Protection
CURRENT & Hz	Measures Current & Frequencies, AC & DC In Dual Display
ERGONOMIC STREAMLINE DESIGN	Fits Comfortably In One's Hand
TRANSIENT PROTECTION	Up To 12kV 1.2/50µs Lightning Surge; Superb Protection For Serious Users
EMC	Meets EN61326-1:2013
LVD SAFETY	Meets EN61010-1 ED. 3.0, EN61010-2-030 ED. 1.0 & EN61010-2-033 ED. 1.0 To CAT IV 1kV
PROTECTIVE HOLSTER	With Holders For Probe Storage And "Third Hand" Feature, Replaceable & Washable
AC, AC+DC 100kHz TRUE RMS	For Non-Sinusoidal Waveforms Of Complex Voltage Or Current Signals
INTELLIGENT AUTO-POWER-OFF	To Extend Battery Life. I-APO Resets On Significant Operation & Measurements
BEEP-JACK AUDIBLE & VISIBLE WARNING	Guards Against Improper Current Terminals Plug In. Decreases Risks Of Damage
PC INTERFACE CAPABILITY	Optional Purchase USB Cable With Data Recording PC Software For Win7/8/10
VFD V & Hz FEATURE	Measures Fundamental Voltage & Frequency Of Most Variable Frequency Drives
dBm FUNCTION	With 20 Selectable Reference Impedance Values
Hz OF LINE LEVEL VOLTAGE	Measures Noisy High Voltage ACV Frequencies Up To 200kHz In Dual Display
HIGH IMPEDANCE VOLTAGE	1000VAC/DC Measuring Capabilities; High Input Impedance For Load Sensitive Circuits
LOGIC LEVEL Hz	Measures Digital Logic Level Frequencies Up To 1MHz
LOGIC LEVEL DUTY%	Measures Digital Logic Level Duty Cycle % Readings
CREST (PEAK HOLD)	Captures Instantaneous +Peak & -Peak, Auto-Ranging
FUNCTION SELECTION	Toggle Conveniently Between Primary & Secondary Functions
PAPER-WHITE DISPLAY BACKLIGHT	For Easy Viewing In The Dark
AUTO & MANUAL-RANGING	Auto-Ranging With Manual-Ranging Override